



PRODUCT DIMENSIONS & SPECIFICATIONS

DA SERIES ALUMINUM UNCASED UPFLOW/DOWNFLOW COILS



Representative drawing only.
Some models may vary in appearance.

STANDARD SPECIFICATIONS

- Riffled Aluminum tubing, enhanced Aluminum fins
- Air pressure tested at 500 psi, leak tested with helium, then sealed and nitrogen pressurized
- Left- or right-hand refrigerant and plumbing connections
- Externally mounted flowrator body with Schrader valve for hiss-testing
- Heavy duty plastic or metal drain pans
- Upflow without field modification. Downflow application require field kit (included)
- AHRI certifiable with all brand of AC and HP systems
- ETL listed for use with both R-22 and R-410A when proper metering device is used
- Ten year limited warranty

POPULAR OPTIONS:

- Factory or field-installed TXV
- Powder painted stainless steel drain pan

COIL MODEL	FLOWRATOR SIZE		DIMENSIONS						SHIPPING INFORMATION			
			PAN WIDTHS (W)"				PAN DEPTH (D)"	BARE SLAB HEIGHT (H)"	SHIPPING WEIGHT (LBS)			SKID QTY
			R 22	R 410a	13	16			19-1/2	23	2 ROW	
DA24A*	0.059	0.055	13	16	19 1/2		19 3/8	13 1/2	11	16	21	30
DA24B*	0.059	0.055	13	16	19 1/2		19 3/8	15 1/2	12	18	24	25
DA24C*	0.059	0.055	13	16	19 1/2		19 3/8	17 1/2	14	22	28	25
DA24D*	0.059	0.055	13	16	19 1/2		19 3/8	19 1/2	15	24	32	20
DA30A*	0.068	0.059	13	16	19 1/2		19 3/8	15 1/2	12	18	24	25
DA30B*	0.068	0.059	13	16	19 1/2		19 3/8	17 1/2	14	22	28	25
DA30C*	0.068	0.059	13	16	19 1/2		19 3/8	19 1/2	15	24	32	20
DA30D*	0.068	0.059	13	16	19 1/2		19 3/8	21 1/2	17	27	35	16
DA36A*	0.074	0.068	13 FOR 2,3R; 16 FOR 4R	16	19 1/2		19 3/8	17 1/2	14	22	28	25
DA36B*	0.074	0.068	13 FOR 2,3R; 16 FOR 4R	16	19 1/2		19 3/8	19 1/2	15	24	32	20
DA36C*	0.074	0.068	13 FOR 2,3R; 16 FOR 4R	16	19 1/2		19 3/8	21 1/2	17	27	35	16
DA36D*	0.074	0.068	13 FOR 2,3R; 16 FOR 4R	16	19 1/2		19 3/8	23 1/2	19	29	38	12
DA42A*	0.080	0.074		16	19 1/2	23	19 3/8	19 1/2	15	24	32	20
DA42B*	0.080	0.074		16	19 1/2	23	19 3/8	21 1/2	17	27	35	16
DA42C*	0.080	0.074		16	19 1/2	23	19 3/8	23 1/2	19	29	38	12
DA42D*	0.080	0.074		16	19 1/2	23	19 3/8	25 1/2	20	32	42	12
DA48A*	0.084	0.080		16	19 1/2	23	19 3/8	21 1/2	17	27	35	16
DA48B*	0.084	0.080		16	19 1/2	23	19 3/8	23 1/2	19	29	38	12
DA48C*	0.084	0.080		16	19 1/2	23	19 3/8	25 1/2	20	32	42	12
DA48D*	0.084	0.080		16	19 1/2	23	19 3/8	27 1/2	22	35	46	12
DA60A*	0.092	0.089			19 1/2	23	19 3/8	25 1/2	20	32	42	12
DA60B*	0.092	0.089			19 1/2	23	19 3/8	27 1/2	22	35	46	12
DA60C*	0.092	0.089			19 1/2	23	21 3/4	27 1/2	25	39	52	12
DA60D*	0.092	0.089			19 1/2	23	21 3/4	31 1/2	29	45	60	12

Notes: 1) Do not use plastic drain pans on oil furnaces or other applications where outlet temperatures may exceed 290 F. Specialty metal drain pans used for these applications.
2) Metal drain pan 3) For all coils - Liquid line 3/8 ODS, suction line 3/4" ODS for DA24-36, 7/8" for DA42-60

Phone: 281.441.6500
Toll Free: 800.423.9007
Fax: 281.441.6510
www.aspenmfg.com



* For complete warranty details visit www.aspenmfg.com.

Revised 10/25/19. In keeping with its policy of continuous progress and product improvement, Aspen reserves the right to make changes without notice and incurring obligation. © 2019